



B16.47 SERIES A ابعاد رینگ داخلی واشرهای اسپیرال برای فلنچ های

ASME B16.20

ASME B16.20-2007

CLASS	150		300		400		600		900	
SIZE	ID	OD	ID	OD	ID	OD	ID	OD	ID	OD
26	654.1	674.6	654.1	687.3	660.4	687.3	647.7	687.3	660.4	687.3
28	704.9	725.4	704.9	738.1	711.2	738.1	698.5	738.1	711.2	738.1
30	755.7	776.2	755.7	795.3	755.7	795.3	755.7	795.3	768.4	795.3
32	806.5	827.0	806.5	852.4	812.8	852.4	812.8	852.4	812.8	852.4
34	857.3	877.8	857.3	903.2	863.6	903.2	863.6	903.2	863.6	903.2
36	908.1	928.6	908.1	957.3	917.7	957.3	917.7	957.3	920.8	960.4
38	958.9	979.4	952.5	979.4	952.5	973.1	952.5	992.1	1009.7	1036.6
40	1009.7	1030.2	1003.3	1023.9	1000.3	1027.2	1009.7	1049.3	1060.5	1100.1
42	1060.5	1081.0	1054.1	1074.7	1051.1	1078.0	1066.8	1106.4	1111.3	1150.9
44	1111.3	1131.8	1104.9	1131.8	1104.9	1131.8	1111.3	1163.6	1155.7	1208.0
46	1162.1	1182.6	1152.7	1179.6	1168.4	1195.3	1162.1	1214.4	1219.2	1271.5
48	1212.9	1233.4	1206.5	1236.7	1206.5	1246.1	1219.2	1271.5	1270.0	1322.3
50	1263.7	1284.2	1244.6	1296.9	1257.3	1296.9	1270.0	1322.3	-----	-----
52	1314.5	1335.0	1320.8	1347.7	1308.1	1347.7	1320.8	1373.1	-----	-----
54	1358.9	1385.8	1352.6	1404.9	1352.6	1404.9	1378.0	1430.3	-----	-----
56	1409.7	1436.6	1403.4	1455.7	1403.4	1455.7	1428.8	1481.1	-----	-----
58	1460.5	1487.4	1447.8	1512.8	1454.2	1506.5	1473.2	1538.2	-----	-----
60	1511.3	1538.2	1524.0	1563.6	1517.7	1570.0	1530.4	1595.4	-----	-----

<p>The Out Side Diameters Inner Ring Tolerance:</p> <p>The Tolerance For Size 26 Through Size 34 :±0.8mm</p> <p>The Tolerance For Size 36 Through Size 60 :±1.3mm</p>	<p>The InSide Diameters Inner Ring Tolerance:±3</p>
---	---